

PRODUCT BROCHURE



Hydraulic System Division

Product Overview



Power Unit



Cylinder



Lubrication Unit



Flushing Unit



Porta Filter Unit



Manifold Block



Hose, Pipe fitting, Flanges



Erection & Commissioning Assistance

Applications



Plate Rolling Mill



Bar Rolling Mill



Furnace Pusher



Compound Impactor



Cone Crusher



Roll Crusher



Ring Granulator



Paper Machine



Press Machine



Machine Tools

Customized Power Unit – Features

Pressure up to 315 bar



Flow up to 100 gpm

TEFC Motor

Plate Oil Cooler

IP56 JB

Dust Proof Enclosure



Energy Efficient Motors

- Lower Operation Cost
- Longer Service Life
- Low Noise Level

Quality Components

- Increased System Efficiency
- Reduced System Downtime

Modular Design

- Reduced System Piping
- Reduced Space Requirement
- Zero Leakage

Other

- Tank conform to DIN 24 339
- GGG40 Manifold Blocks
- Absolute Filtration
- PLC Control Panel (Optional)

Standard & Customized Cylinders

Pressure up to 350 bar

Piston Ø 40 to 320mm

Piston Rod Ø 22 to 220mm

Stroke up to 4m

6 Type of Mounting



Heavy Wall Steel Tubes

Honed to High Surface Finish

Confirm to ISO 6022 / DIN 24333

Cylinder Body

Case Hardened

Chrome Plated

Adjustable Cushion

Piston Rod

Viton / Nitrile / PTFE

Up to 90 degC

Parker / Hunger Make

Special Design

Seals

Mant. Free Spherical Bearings

Position Switch

Rubber Bellow

Other Option